

ICON PTZ HD NDI

1.317,00 € tax included

Reference: ICPTZHDND1



ICON PTZ HD NDI

Professional PTZ HD NDI Camera for live broadcasting, POE, Full HD 1080p50/60 , SONY 1/2.8" Progressive CMOS sensor 3.50 Megapixel, 20X optical zoom+58.7° view angle, Output: HDMI+SDI+USB+IP, RS232 In/out, RS422, 1080p, auto focus, IR remote, Minimum Illumination 0.35 lux.

Features

Lens & Wide Angle: 20X optical zoom

Full HD 1080p50/60, 1/2.8" Sony CMOS Sensor, 3.5 Megapixels;

Interface: HDMI+SDI+USB+IP (POE optional) + LINE-IN+RS232-IN/OUT+RS422

Internet protocol support: RTSP/RTMP, ONVIF, Supports NDI/HX

DUAL IP-Stream H265/H264 and MJPEG compression enabling FULL HD video stream by ultra low bandwidth over RTMP, RTSP, TCP/IP, HTTP, etc

Wall mounting, desktop or ceiling mounting.

Full compatibility with SONY terminal.

Image Sensor: 1/2.8" Sony CMOS Sensor

Effective Pixels: 3.50 Megapixels

Resolution: 1080p60/50, 1080i60/50, 1080i59.94, 1080p/30, 1080p/25

Signal System: PAL/NTSC

Lens 20X optical zoom, f=4.7mm(wide)~94.0 mm(far end) F1.6~F2.8

Horizontal View Angle: 58.7°W?3.2°T?

Pan: 355°(max. speed:80°/s)

Tilt: -30° to +90° (max. speed: 60°/s)

Focus System: Auto/Manual

S/N Ratio: ?50db

Preset Position: 9 preset positions by IR remote controller, 255 preset positions by Keyboard or PC

Minimum Illumination: 0.35Lux

Exposure Control: Auto/Manual/Priority AE/Exposure Compensation/Bright

Shutter Speed: 1/1~1/10,00S

Gain: Auto/Manual

White Balance: Auto/Manual/ATW/One-click/Indoor/Outdoor

Image Effect: Full color/black and white/electronic flip

Video Output: HD HDMI, 3G-SDI,USB2.0, IP,POE(optional) ,Line in

Control Protocol: SONY VISCA, PELCO P/D

Control Mode: RS-232C, RS-422/485

Power: 12 DC(10.8~13.0DC)

Power Consumption: Max. 30W(DC 12V)

Operating Temperature: 0~40?

Storage Temperature: -20-60?

Camera Dimension: ?L?170×?W?151×?H?190mm

Weight: 1320g

Accessories: DC 12V power adapter, IR Remote, Operation manual, RS-232C Cable, HDMI cable, USB Cable , Ceiling bracket