

CARVER PT-2400

1.999,00 € tax included

Reference: CAPT2400



CARVER PT-2400 FINALE STEREO 2x750W/8

Power Output:

Both channels driven (20Hz-20kHz)

8 ohm/ch. 750 watts

4 ohm/ch. 1200 watts

2 ohm/ch. 1500 watts

Power Output: Series mono operation (20Hz-20kHz)

8 ohm 2400 watts

4 ohm 3000 watts

Signal to Noise Ratio: >100dB

(from rated power @ 4?/A weighted)

Frequency Response: 20Hz to 20kHz ± 0.5 dB

Channel Separation: >55db @ 1kHz

Slew Rate: 25V/ μ s

THD: 4? 20-20kHz (at 1200W) IM Distortion: 200 @ 1kHz

Sensitivity: 1.5 V rms

Gain: 34dB

Input Impedance: 15 Kilohms

Unbalanced 30 Kilohms

Balanced CMRR: >70db @ 1kHz

Maximum Current Draw: 40 A (4? rated power)

Display: 7 LED indicators per channel, 1 green on,

5 yellow signal, 1 red clip/protect

Cooling: Rear to front w/100 CFM maximum

Connections-Input:

XLR, barrier strip

Output: 5-way binding posts, 2 sets/channel

Size (HxWxD): 5.25" (3u) x 19" x

12.75" (133mm x 483mm x 324mm)

Net Weight: 48 lbs. (21.8 Kgs.)

Shipping Weight: 59 lbs. (26.8 Kgs.)

Due to ongoing research and development, all specifications and features effective 4/96 are subject to change without notice.