CARVER PT-2400

1.999,00 € tax included

Reference: CAPT2400



CARVER PT-2400 FINALE STEREO 2x750W/8

Power Output:

Both channels driven (20Hz-20kHz)
8 ohm/ch. 750 watts
4 ohm/ch. 1200 watts
2 ohm/ch. 1500 watts

Power Output: Series mono operation (20Hz-20kHz)
8 ohm 2400 watts
4 ohm 3000 watts

Signal to Noise Ratio: >100dB
(from rated power@4?/A weighted)
Frequency Response: 20Hz to 20kHz ±0.5dB
Channel Seperation:>55db @ 1kHz
Slew Rate: 25V/µs
THD:4? 20-20kHz (at 1200W) IM Distortion: 200 @ 1kHz
Sensitivity: 1.5 V rms
Gain: 34dB
Input Impedance: 15 Kilohms
Unbalanced 30 Kilohms
Balanced CMRR:>70db @ 1kHz
Maximum Current Draw: 40 A (4? rated power)
Display: 7 LED indicators per channel, 1 green on,
5 yellow signal, 1 red clip/protect
Cooling: Rear to front w/100 CFM maximum
Connections-Input:
XLR, barrier strip
Output: 5-way binding posts, 2 sets/channel
Size (HxWxD): 5.25” (3u) x 19” x
12.75” (133mm x483mm x 324mm)

Net Weight:48 lbs. (21.8 Kgs.)
Shipping Weight: 59 lbs. (26.8 Kgs.)
Due to ongoing research and development, all specifications and features effective 4/96 are subject to change without notice.