KME VL6I PASSIVE 2-WAY LOUDSPEAKER



376,00 € tax included

Reference: KMVL6IBK

KME VL6I PASSIVE 2-WAY LOUDSPEAKER

The new VL 6 i is a passive 2-way installation loudspeaker with extremely brilliant and clear sound quality. It is designed for music and speech reproduction as top unit, in combination with a VERSIO subwoofer or as fullrange speaker. Meeting and seminar rooms, churches and theatres, multimedia presentations, surround sound applications, clubs and discotheques, restaurants, near field sound distribution

Specifications:
Components: 6" + 1" Neodymium
Dispersion (h x v): 85° x 55° Waveguide elliptical
Nominal load AES/prog. (watts): 200 / 400
Impedance (Ohm): 8
SPL (nom./max.) dB: 93 / 116
Frequency range: 80 Hz - 19 kHz
Crossover frequency (Hz/24dB): 2.000
Connectors: 2 x terminal screw connectors, 2 x Speakon optional
Finish: PU coating black (white optional), weather resistant' impregnation of loudspeaker membrane
Special features: 10 M8 treads, Protection class IP 44
Protective grille: high protective comb grid with acoustic foam
Dimensions (W x H x D) mm: 235 x 405 x 190
Weight (kg): 7
Design: top unit / fullrange