TASCAM CD-500B

459,00 € tax included

Reference: TACD500B

TASCAM CD-500B - CD PLAYER 1U



LETTORE CD MP3 CON USCITE BILANCIATE

Il CD-500B è un riproduttore di CD super compatto' un lettore con caricamento a slot frontale ed un affidabile motore senza spazzole rendono il CD 500B un prodotto molto versatile e moderno. Vi è poi un set completo di funzioni ideali per studi broadcast, studi di registrazione, teatri, società di noleggio audio e video, palestre ed ogni altra installazione permanente. L'apparecchio, oltre alle funzioni standard di riproduzione e riproduzione, ne offre molte altre per l'uso professionale. Tra queste: il "flash start", "auto cue" (ricerca dell'inizio di un brano), l' "auto ready" (pausa automatica alla fine di un brano), la funzione "call" (ritorno alla posizione da cui era partita l'ultima lettura), il "pitch control" (±16%) con la possibilità di variare il tempo lasciando inalterata l'intonazione, l' "intro-check" o il "fade in / fade out". Per l'integrazione in apparecchiature di controllo e in installazioni fisse sono disponibili: la riproduzione controllata Relay, partenza controllata da fader, segnale EOM (fine del messaggio) e una porta seriale. Il CD-500B può inoltre memorizzare diverse condizioni di funzionamento, come riavviare la riproduzione automaticamente all'accensione.
Specifiche tecniche
AUDIO OUTPUTS
Analog output (unbalanced): RCA pin jack
Nominal output level: –10 dBV
Maximum output level: +6 dBV
Output impedance: Less than 1 kOhm
Analog output: (balanced, CD-500B only) XLR-3-32 (1: GND 2: Hot 3: Cold)
Nominal output level: +4 dBu
Maximum output level: +20 dBu
Output impedance: 150 Ohm
Phones output: 6.3mm stereo phone jack
Maximum output power :45 mW + 45 mW (1kHz, THD at 0.1%, 32 ohm loaded)
Digital output (Optical): TOS (JEITA RC-5720C)
Format: IEC60958-3 (SPDIF)
Digital output (Coaxial): RCA pin jack
Format: IEC60958-3 (SPDIF)
Digital output (AES/EBU, CD-500B only):XLR-3-32
Format: AES3-2003 / IEC60958-4 (AES/EBU)
OTHER INPUTS AND OUTPUTS
RELAY input/output: 3.5 mm mini jack

RS-232C: D-sub, 9-pin
REMOTE: 2.5 mm TRS jack (for Tascam RC-3F footswitch)
PARALLEL (CD-500B only): D-sub, 15-pin
AUDIO PERFORMANCE
Frequency response: 20 Hz – 20 kHz, ±0.5dB
THD + N 95 dB
Channel separation: >95 dB
POWER SUPPLY AND OTHER SPECIFICATIONS
Power supply: 100–240 V AC, 50–60 Hz
CD-500B: 11 W
Dimension (W x H x D): 483 mm x 45 mm x 301 mm
Weight: 3.7 kg