

## KME MCX10 PANO COMPACT HIGH-PERFORMANCE COAXIAL STAGE MONITOR

**2.150,00 € tax included**

Reference: KMMCX10

KME MCX10 PANO COMPACT HIGH-PERFORMANCE COAXIAL STAGE MONITOR



The MCX 10 is a compact high-performance coaxial stage monitor. Depending on the application, the design enables three set-up options: 35° angle for monitoring from short distances, 55° for longer distances, and 90° e.g. for front-fill applications at the stage edge. Due to its inconspicuous design, the MCX 10 fits harmoniously and elegantly into all surroundings. The speaker features a broad dispersion of 70°.

The highly sturdy monitor convinces with its precise sound reproduction and gives musicians on stage a top-class sound experience. The flange inside the handle provides the possibility to use the MCX 10 as a PA system on a high stand. If required, the MCX 10 combines perfectly with the QLB 215 or QLB 118X/G subwoofers.

The monitor offers three Neutrik NL4 speakon connectors.

Two of them are placed on the side of the high stand flange.

- Components: 10" + 1.3" (2.5" voice coil), coaxial
- Dispersion (h x v): 70° conical
- Nominal load AES / Program (Watt): 300 / 600
- Impedance (Ohm): 8
- SPL nom / max (\*dB): 95 / 120
- Frequency range (-6 dB): 70 Hz – 19 kHz
- Crossover frequency (Hz): 1300 Hz
- Connectors: 3x Speakon NL4 (2x right, 1x left)
- Special features: 2x butterfly handle four sided, 2x M8 mounting thread, 1x M8 safety thread
- Finish: PU coating (black)
- Protective grille: sturdy front grille with acoustic foam
- Protection class: IP 44
- Dimensions W/H/D (mm): 405 x 325 x 400
- Weight (kg): 15
- Application: low profile stage monitor with 3 possible positions (35°, 55°, 90°) and integrated high stand flange
- Recommended system amplifier (preset): DA428 (monitor/top preset)
- System extension (recommendation): Subwoofer extensions: QLB 215, QLB 118X/G
- Accessories (optional): M8 eyebolts, protective cover, transport case