KME VLX12 VERSIO X PASSIVE SPEAKER 1x12" - 350W - 2WAY



1.199,00 € tax included

Reference: KMVLX12

KME VLX12 VERSIO X PASSIVE SPEAKER 1x12" - 350W - 2WAY

The VLX12 is a passive 2-way loudspeaker which is both suitable for speech and music reproduction as a top, fullrange speaker, or stage monitor.

Multifunctional:
- enclosure design enabling several setup variants (speaker stand, monitor, frontfill)
- compact dimensions and moderate weight due to neodymium speaker
- speaker flange with adjustable angle
- flying ability due to optional flying hardware

Durable and value stable:
- Wooden casing with weatherproof PU coating
- High quality and high load capacity components
- Impregnated loadspeaker membrane for inside and outside applications

Sound:
- Smooth and balanced reproduction of the high frequencies
- Low acoustic feedback behaviour
- Natural and transparent sound

Specifications:
- components: 12“ + 1“ (1.4“ voice coil)
- dispersion: 85° x 55° elliptical
- nominal load AES/program (Watt): 350 / 700
- impedance (ohms): 8
- SPL nom./max. (dB): 97 / 122
- frequency range (-10dB): 60 Hz – 20 kHz
- connectors: 2x Neutrik Speakon NL4
- finishing: PU coating (black or white)
- protective grills: sturdy front grille with acoustic foam
- special features: 2x M8 mounting thread, 1x M8 safety thread, speaker stand receptacle with adjustable angle, 1x handle
- dimensions W x H x D (mm): 390 x 610 x 360

- weight (kg): 17