KME VLX2 VERSIO X PASSIVE 2-WAY LOUDSPEAKER



429,00 € tax included

Reference: KMVLX2

KME VLX2 VERSIO X PASSIVE 2-WAY LOUDSPEAKER

The VLX 2 is a passive 2-way loudspeaker with d'Appolito design in a discreet mini size format, which is equally suitable for speech or music reproduction at moderate signal levels with its linear frequency response.

Multifunctional
- Ultra-compact and unobtrusive enclosure design (assembly on speaker stand or flying application)
- compact dimensions and moderate weight
- integrated speaker flange
- flying and mounting abilities due to optional hardware

Durable and value stable:
- Wooden casing with weatherproof PU coating
- High quality and high load capacity components
- Impregnated loadspeaker membrane for inside and outside applications

Sound:
- Smooth and balanced reproduction of the high frequencies
- Low acoustic feedback behaviour
- Natural and transparent sound

Specifications:
- components: 2x 4" + 1x 1" dome tweeter
- dispersion: 80° x 40°
- nominal load AES/program (Watt): 125 / 250
- impedance (ohms): 16
- SPL nom./max. (dB): 88 / 112
- frequency range (-10dB): 120Hz - 19 kHz
- connectors: 2x Neutrik Speakon NL4
- finishing: PU coating (black or white)
- protective grills: sturdy front grille with acoustic foam
- special features: 2x M8 mounting thread, 1x M8 safety thread, speaker stand receptacle, 1x handle
- dimensions W x H x D (mm): 135 x 290 x 166

- weight (kg): 3,5