TASCAM GB10 GUITAR/BASS TRAINER

149,00 € tax included

Reference: TAGB10



TASCAM GB10 GUITAR/BASS TRAINER

TASCAM GB10 GUITAR/BASS TRAINER

Il GB-10 è un trainer/registratore per chitarra e basso. Come la ben nota serie di allenatori e registratori Tascam CD e MP3, questo modello può rallentare e mettere in loop file audio MP3 o WAV senza cambiare l'intonazione, per aiutare i musicisti a imparare nuovi brani e ritornelli. Il GB-10 dispone di un ingresso da 6,3 mm per chitarra ed effetti come amp modeling, delay e riverbero per far pratica usando una cuffia. Si può regolare il bilanciamento dello strumento con la musica di sottofondo. Sono inclusi anche un accordatore e un metronomo per una precisa riproduzione, e un ingresso pedale permette il controllo a mani libere di diverse funzioni. Il GB-10 offre funzioni di registrazione a qualità CD con possibilità di sovraincisione ed elaborazione di arrangiamenti personali. Una card SD da 2 GB è inclusa nell'unità e il nuovo design da tavolo lo rende uno strumento perfetto per gli studenti di musica, hobbisti o professionisti che vogliono perfezionare la propria abilità.

Specifiche tecniche

GENERAL

- Recording media: SD card (64 MB - 2 GB)
- SDHC card: (4-32 GB)
- Recording format: WAV (44.1kHz, 16-bit)
- Playback formats: WAV (44.1 kHz, 16/24-bit)
- MP3 (44.1/48 kHz, 32/64/96/128/192/256/320 kbit/s)
- Number of input channels: 1 (mono)
- Dimensioni: 158 x 30 x 70 mm
- Peso: 160 g

AUDIO INPUTS AND OUTPUTS

- Guitar input: 6.3-mm jack, mono
- Input impedance: 800 kOhm
- Nominal input level: -13 dBV (INPUT volume at 7)
- Maximum input level: +3 dBV (INPUT volume at 7)
- Minimum input level: -25 dBV (INPUT volume at 10)
- Headphones/line output: 3.5-mm mini jack, stereo
- Output impedance: 23 Ohm

- Nominal output level: -14 dBV (10 kOhm load)
- Maximum output level (line): +2 dBV (10 kOhm load)
- Maximum output power (headphones): 15 mW + 15 mW (32 Ohm load)

OTHER INPUTS AND OUTPUTS

- USB port: Mini-B type connector
- Format: USB 2.0 High Speed (480 Mbit/s)
- Remote connector: 2.5-mm TRS jack

AUDIO PERFORMANCE

- Frequency response: 20 Hz - 20 kHz +1/-5 dB (Fs = 44.1 kHz)
- Total harmonic distortion: 0.07% (Fs = 44.1 kHz)
- S/N ratio: 70 dB

Requisiti minimi di sistema

- **Windows: Pentium 300 MHz or faster, 128 MB or more memory, USB port (USB 2.0 recommended)**
- **Macintosh: Power PC, iMac, G3, G4 266 MHz or faster, 64 MB or more memory, USB port (USB 2.0 recommended)**
- **Recommended USB host controller: Intel chipset**
- **Supported operating systems: Windows XP , Windows Vista , Windows 7, Mac OS X 10.2 or later**