

BLACKMAGIC DESIGN HyperDeck Studio HD Mini

572,00 € tax included

Reference: BLHDSHDMINI



CONVERTITORE HYPERDECK STUDIO HD MINI

Il più compatto degli HyperDeck Studio ricalca le dimensioni dei convertitori Teranex Mini. Il design modulare permette di affiancare 3 HyperDeck Studio HD Mini, o una combinazione di deck e switcher, convertitori o processori di streaming, in una singola unità rack sulla mensola Teranex Mini Rack Shelf. Anche se piccolo, offre funzioni avanzate come ingresso e uscita 3G-SDI, uscita HDMI, due slot per schede SD, generatori di sync e timecode integrati, pannello di controllo frontale e alimentazione AC e DC. Puoi anche collegare HyperDeck Studio HD Mini al computer tramite USB, che lo rileva come una webcam, e usare qualsiasi software video.

Caratteristiche

SDI Video I/O: 1

SDI Rates: 270Mb, 1.5G, 3G

HDMI Video Outputs: 1

Screen: 2.2 inch LCD

Timecode Connections: 1xBNC In, 1xBNC Out

Reference Connections: 1 x BNC In, 1 x BNC Out. Tri-Sync or Black Burst

SDI Audio Inputs: 16 channels embedded audio

SDI Audio Outputs: 16 channels embedded audio

HDMI Audio Outputs: 8 channels embedded audio

Remote Control: 1xRS-422 In

Recorder Configuration: Via user interface o Blackmagic HyperDeck

Ethernet: 1Gb/s

Computer Interface: 1xUSBType-C 3.0(up to 5Gb/s)

SD Video Standards: 525i59.94 NTSC, 625i50PAL

HD Video Standards: 720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60...2Kp30DCI

SDI Compliance: SMPTE259M, SMPTE292M, SMPTE296M, SMPTE372M, ecc...

Supported HDMI Formats: 525i59.94NTSC, 625i50PAL, 720p50, 720p59.94, 720p60,1080i50, 1080i59.94, 1080i60, ecc...

Audio Sampling: Television standard 24?bit, 48kHz samplerate

Video Sampling: 4:2:2 YUV

Color Precision: 10?bit

Color Space: REC601, REC709, REC2020

HDR Support: Hybrid Log?Gamma, ST2084300, ST2084500, ST2084800, ST20841000, ST20842000, ST20844000, ST2084

Media: 2xSD card slots1 x USB-C 3.0

Media Type: UHS-I and UHS-II SD cards

Media Format: ExFAT (Windows/Mac)or HFS+(Mac) filesystems

Codecs Supportati: ProRes HQ QuickTime, ProRes422QuickTime, ProResLTQuickTime, ecc...

Controlli: RS-422 deck control, SDI start/stop, timecode run

Software Incluso: Blackmagic OSBlackmagic HyperDeck, Setup Internal Software UpgradeLoaded at system start, , Blackmagic HyperDeck Setup using USB port

Compatibilità: Mac 10.15 Catalina, Mac 11.1 Big Sur e successivo. Windows 10,64-bit