

## ESI NEVA OTG

**138,00 € tax included**

Reference: NEVAOTG



Scheda Dual USB C (una porta OTG) con 2 In e 2 Out analogici - In Preamp e Hi-Z - Uscita cuffia

### USB-C Audio Interface

- 24 bit / 192 kHz digital converter
- +48 V phantom power switchable
- Two mic/line inputs: XLR / 6.3 mm jack combo balanced
- AD converter with 97 dB(a) dynamic range / DA converter with 107 dB(a) dynamic range
- Two line outputs: 6.3 mm jack balanced
- Stereo headphone output: 6.3 mm jack
- Loopback function
- Two USB-C ports
- USB bus-powered
- Connection to mobile devices (e.g. iPhone, iPad, other smartphones or tablets) via the secondary USB-C OTG connection (USB 2.0 audio interface) or via TRRS analogue audio cable
- EWDM driver for Windows 10 / 11 with ASIO 2.0, MME, WDM and DirectSound support
- Supports OS X / macOS (10.9 and higher) via the native CoreAudio USB driver from Apple
- Class compliant
- Dimensions (W x D x H): 170 x 120 x 44 mm
- Weight: 450 g
- Includes USB cable (type C to A), Cubasis LE3, Wavelab LE10 and Bitwig Studio 8-Track